

Product information



Product number: DP125S - 24W
 Input Voltage (v): 220-240V~
 Dimming: On/Off, TRIAC, 1-10V, DALI
 Light source: COB LED
 luminaire Lifetime: 50.000h (L80B50, Ta25°C)
 IP Rating: 54
 Working Temperature (°C): -5 ~ +30
 Material: Aluminium
 Fitting Colors: Sandy White / Sandy Black



Packaging information

N.W. lamp (Kg): 0.73
 G.W. Carton (Kg): 15.6
 Master carton dimensions(mm): 475x370x365
 Quantity per carton(PCS): 20

| Beam | Watt | CRI | Luminous | CCT | Code |
|------|------|-----|----------|-------|-------------------|
| 18 | 24W | 90 | 1958 lm | 4000K | DP125S-24G40-S01 |
| | | | 1901 lm | 3000K | DP125S-24G30-S01 |
| | | | 1805 lm | 2700K | DP125S-24G27-S01 |
| 28 | 24W | 90 | 2030 lm | 4000K | DP125S-24G40-M01 |
| | | | 1971 lm | 3000K | DP125S-24G30-M01 |
| | | | 1872 lm | 2700K | DP125S-24G27-M01 |
| 38 | 24W | 90 | 2087 lm | 4000K | DP125S-24G40-F01 |
| | | | 2027 lm | 3000K | DP125S-24G30-F01 |
| | | | 1925 lm | 2700K | DP125S-24G27-F01 |
| 50 | 24W | 90 | 2070 lm | 4000K | DP125S-24G40-WF01 |
| | | | 2010 lm | 3000K | DP125S-24G30-WF01 |
| | | | 1909 lm | 2700K | DP125S-24G27-WF01 |

