


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 86.76 lm/W			
MODEL	BL07-30W-840-W-60	Imax(cd)	2434	S/MH(C0/180)	0.78
NOMINAL POWER(W)	30	LOR(%)	100.0	S/MH(C90/270)	0.75
RATED VOLTAGE(V)	226	TOTAL FLUX(lm)	2533.5	η UP,DN(C0-180)	1.4,48.1
NOMINAL FLUX(lm)	2533.5	CIE CLASS	DIRECT	η UP,DN(C180-360)	1.4,49.1
LAMPS INSIDE	1	η up(%)	2.8	CIBSE SHR NOM	0.75
TEST VOLTAGE(V)	226.6	η down(%)	97.2	CIBSE SHR MAX	0.90

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:QiuMing
Test Date:2015-10-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:5.920m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	lum, lamp
10	2142	2128	2103	2097	2106	2119	2148	2142	0- 10	217.1	217.1	8.57,8.57
20	1551	1545	1501	1489	1499	1517	1537	1537	10- 20	506.7	723.8	28.6,28.6
30	1542	1579	1522	1499	1555	1574	1612	1584	20- 30	688.2	1412	55.7,55.7
40	795.2	801.2	776.4	780.3	780.7	790.4	809.6	812.4	30- 40	648.5	2061	81.3,81.3
50	67.39	61.99	57.04	61.69	58.49	56.71	61.68	64.09	40- 50	335.8	2396	94.6,94.6
60	27.91	27.28	26.32	26.38	25.57	25.89	27.43	28.49	50- 60	37.54	2434	96.1,96.1
70	8.473	8.358	8.059	8.150	8.454	8.504	9.025	8.910	60- 70	16.71	2451	96.7,96.7
80	5.601	5.737	5.919	6.001	6.099	5.927	5.747	5.703	70- 80	6.525	2457	97,97
90	4.742	4.562	4.641	4.617	4.917	4.970	5.796	5.500	80- 90	6.394	2464	97.2,97.2
100	5.633	5.592	5.698	5.761	6.315	6.235	6.101	6.186	90-100	5.746	2469	97.5,97.5
110	7.539	7.311	7.488	7.582	8.458	8.284	8.169	8.383	100-110	7.341	2477	97.8,97.8
120	9.564	9.298	9.486	9.661	10.52	10.19	10.02	10.33	110-120	8.792	2485	98.1,98.1
130	12.23	11.90	12.05	12.41	13.10	12.58	12.41	12.83	120-130	9.949	2495	98.5,98.5
140	15.33	14.94	15.12	15.65	15.88	15.12	14.98	15.50	130-140	10.70	2506	98.9,98.9
150	18.27	18.08	18.41	18.80	18.29	17.37	17.27	17.85	140-150	10.48	2517	99.3,99.3
160	20.14	20.50	20.99	21.01	20.15	19.25	19.07	19.57	150-160	8.808	2525	99.7,99.7
170	22.02	22.97	23.64	23.33	22.99	22.60	22.04	22.22	160-170	6.022	2531	99.9,99.9
180	21.93	22.04	21.98	21.82	21.98	22.01	22.02	21.80	170-180	2.157	2534	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:QiuMing
Test Date:2015-10-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:5.920m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:QiuMing
Test Date:2015-10-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:5.920m [K=1.0000]
Remarks:

WEC AND CCEC

NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:

pcc	80%	70%	50%	30%	10%	0
pw	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
pfc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Wall Exitance Coefficients(WEC)
0.0						
1.0	.197 .112 .035	.189 .108 .034	.175 .100 .032	.162 .093 .030	.150 .087 .028	
2.0	.189 .104 .032	.182 .101 .031	.170 .095 .029	.159 .089 .028	.149 .084 .026	
3.0	.180 .096 .029	.175 .094 .028	.164 .089 .027	.154 .085 .026	.145 .080 .025	
4.0	.172 .089 .026	.167 .087 .026	.158 .084 .025	.149 .080 .024	.141 .077 .023	
5.0	.164 .083 .024	.159 .082 .024	.151 .079 .023	.144 .076 .023	.136 .073 .022	
6.0	.156 .078 .022	.152 .077 .022	.145 .074 .022	.138 .072 .021	.132 .069 .021	
7.0	.149 .074 .021	.146 .073 .021	.139 .070 .020	.133 .068 .020	.127 .066 .019	
8.0	.142 .070 .020	.139 .069 .019	.133 .067 .019	.128 .065 .019	.122 .063 .018	
9.0	.136 .066 .018	.133 .065 .018	.128 .063 .018	.123 .061 .018	.118 .060 .017	
10.0	.130 .062 .017	.128 .062 .017	.123 .060 .017	.118 .059 .017	.113 .057 .016	

pcc	80%	70%	50%	30%	10%	0
pw	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
pfc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Ceiling Cavity Exitance Coefficients(CCEC)
0.0	.212 .212 .212	.181 .181 .181	.123 .123 .123	.071 .071 .071	.023 .023 .023	
1.0	.194 .178 .165	.166 .153 .142	.113 .105 .098	.065 .061 .057	.021 .020 .018	
2.0	.180 .154 .132	.154 .132 .114	.106 .092 .079	.061 .053 .047	.020 .017 .015	
3.0	.169 .135 .108	.145 .117 .094	.099 .081 .066	.057 .047 .039	.018 .015 .013	
4.0	.159 .121 .091	.137 .104 .079	.094 .073 .056	.054 .043 .033	.018 .014 .011	
5.0	.151 .110 .079	.130 .095 .068	.090 .066 .048	.052 .039 .029	.017 .013 .009	
6.0	.145 .101 .069	.124 .087 .060	.086 .061 .043	.050 .036 .025	.016 .012 .008	
7.0	.138 .093 .062	.119 .081 .054	.082 .057 .038	.048 .033 .023	.015 .011 .008	
8.0	.133 .087 .056	.114 .076 .049	.079 .053 .035	.046 .031 .021	.015 .010 .007	
9.0	.128 .082 .052	.110 .071 .045	.076 .050 .032	.044 .030 .019	.014 .010 .006	
10.0	.123 .078 .048	.106 .068 .042	.074 .048 .030	.043 .028 .018	.014 .009 .006	

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:QiuMing
Test Date:2015-10-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:5.920m [K=1.0000]
Remarks:

Uncorrected UGR Table

NAME:						TYPE:					WEIGHT:				
DIM.:						SPEC.:					SERIAL No.:				
MFR.: Rayconn						SUR.:					PROTECTION ANGLE:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions						Viewed crosswise					Viewed endwise				
x = 2H y = 2H						21.3	22.4	21.6	22.6	22.8	21.2	22.2	21.4	22.4	22.6
3H						21.1	22.1	21.5	22.4	22.6	21.0	21.9	21.3	22.2	22.5
4H						21.1	22.0	21.4	22.2	22.5	20.9	21.8	21.2	22.1	22.3
6H						21.0	21.8	21.3	22.1	22.4	20.8	21.6	21.2	21.9	22.3
8H						20.9	21.7	21.3	22.0	22.4	20.8	21.6	21.1	21.9	22.2
12H						20.9	21.7	21.3	22.0	22.3	20.7	21.5	21.1	21.8	22.2
4H 2H						21.1	21.9	21.4	22.2	22.5	20.9	21.8	21.2	22.1	22.3
3H						20.9	21.6	21.2	22.0	22.3	20.7	21.5	21.1	21.8	22.1
4H						20.8	21.5	21.2	21.8	22.2	20.6	21.3	21.0	21.7	22.0
6H						20.7	21.3	21.1	21.7	22.1	20.6	21.2	21.0	21.5	22.0
8H						20.7	21.2	21.1	21.6	22.1	20.5	21.1	21.0	21.5	21.9
12H						20.7	21.2	21.1	21.6	22.0	20.5	21.0	21.0	21.4	21.9
8H 4H						20.6	21.2	21.1	21.6	22.0	20.5	21.0	20.9	21.4	21.9
6H						20.6	21.0	21.0	21.5	21.9	20.4	20.9	20.9	21.3	21.8
8H						20.5	21.0	21.0	21.4	21.9	20.4	20.8	20.9	21.3	21.8
12H						20.6	20.9	21.1	21.4	21.9	20.4	20.8	20.9	21.2	21.8
12H 4H						20.6	21.1	21.0	21.5	22.0	20.4	20.9	20.9	21.4	21.8
6H						20.5	20.9	21.0	21.4	21.9	20.4	20.8	20.9	21.2	21.7
8H						20.5	20.9	21.0	21.3	21.9	20.4	20.7	20.9	21.2	21.7
Variations with the observer position at spacings:															
S = 1.0H						+ 3.5 / - 9.9					+ 3.6 / -10.0				
1.5H						+ 3.5 / - 9.8					+ 3.9 / - 9.4				
2.0H						+ 8.5 / - 6.6					+ 8.0 / - 4.9				

CIE Pub.117 Corrected 2534 lm Total Lamp Luminous Flux.(8log(F/F0) = 3.2)

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:QiuMing
Test Date:2015-10-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:5.920m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	80	72	68	79	72	68	78	72	67	63
0.80	88	81	77	87	81	77	86	80	76	72
1.00	94	87	83	93	87	83	91	87	82	77
1.25	99	93	89	98	92	88	95	91	87	82
1.50	102	96	93	101	96	92	98	94	91	85
2.00	106	101	97	104	100	96	101	97	94	88
2.50	108	103	100	106	102	99	102	99	96	89
3.00	109	106	102	107	104	101	104	101	98	91
4.00	112	108	106	109	107	104	105	103	101	93
5.00	113	110	108	111	108	106	106	104	103	94
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004					Suspended			SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: QiuMing
Test Date: 2015-10-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 γ Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity: 65.0%
Test Distance: 5.920m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:




C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: QiuMing
Test Date: 2015-10-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity: 65.0%
Test Distance: 5.920m [K=1.0000]
Remarks:

AAI Figure

NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: QiuMing
Test Date: 2015-10-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity: 65.0%
Test Distance: 5.920m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: QiuMing
Test Date: 2015-10-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity: 65.0%
Test Distance: 5.920m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: QiuMing
Test Date: 2015-10-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity: 65.0%
Test Distance: 5.920m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	15	30	45	60	75	90	105	120	135	150	165	180	195	210	225	240	255	270
0	2434	2434	2434	2434	2434	2434	2434	2434	2434	2434	2434	2434	2434	2434	2434	2434	2434	2434	2434
5	2355	2357	2349	2352	2344	2349	2343	2347	2341	2348	2343	2348	2350	2345	2355	2349	2358	2353	2361
10	2142	2147	2131	2128	2113	2118	2103	2102	2088	2097	2088	2098	2106	2102	2122	2119	2137	2132	2148
15	1848	1854	1835	1836	1811	1812	1793	1789	1770	1781	1771	1788	1795	1789	1819	1814	1839	1831	1854
20	1551	1557	1545	1545	1525	1521	1501	1500	1482	1489	1484	1495	1499	1494	1519	1517	1537	1528	1537
25	1449	1448	1460	1446	1430	1413	1431	1428	1427	1437	1465	1428	1366	1367	1402	1409	1407	1405	1404
30	1542	1560	1530	1579	1558	1561	1522	1515	1469	1499	1494	1542	1555	1512	1538	1574	1595	1594	1612
35	937	956	966	969	958	958	939	938	927	943	930	942	964	941	957	965	974	972	984
40	795	798	801	801	794	792	776	771	766	780	778	783	781	758	766	790	797	791	810
45	553	545	487	497	445	448	404	415	395	429	419	456	464	440	500	508	549	538	576
50	67.4	68.1	64.8	62.0	59.2	57.6	57.0	56.9	58.1	61.7	64.0	61.3	58.5	56.5	58.3	56.7	58.0	58.8	61.7
55	44.1	43.4	42.2	41.8	40.6	40.5	39.7	39.6	39.3	39.8	38.9	38.6	38.0	37.4	38.9	38.8	39.7	40.2	42.4
60	27.9	27.9	27.3	27.3	26.7	26.9	26.3	26.4	26.0	26.4	25.9	25.9	25.6	25.2	25.9	25.9	26.5	26.3	27.4
65	16.9	17.1	16.7	16.7	16.4	16.5	16.0	16.0	15.8	16.2	16.1	16.4	16.2	16.0	16.6	16.2	16.7	16.7	17.3
70	8.47	8.60	8.28	8.36	8.27	8.39	8.06	8.15	7.87	8.15	7.97	8.37	8.45	8.39	8.79	8.50	8.86	8.73	9.02
75	5.66	5.68	5.74	5.81	5.89	5.94	5.98	6.01	6.06	6.09	6.09	6.06	6.10	6.05	5.99	5.94	5.87	5.83	5.76
80	5.60	5.63	5.68	5.74	5.82	5.88	5.92	5.94	5.97	6.00	6.01	5.98	6.10	6.04	5.98	5.93	5.86	5.81	5.75
85	5.60	5.64	5.69	5.75	5.82	5.88	5.94	5.96	6.00	6.02	6.01	5.99	6.20	6.16	6.09	6.04	5.98	5.93	5.87
90	4.74	4.85	4.58	4.56	4.61	4.60	4.64	4.61	4.65	4.62	4.63	4.59	4.92	4.94	5.00	4.97	5.54	5.30	5.80
95	4.97	4.96	4.99	4.99	5.05	5.05	5.08	5.07	5.09	5.08	5.10	5.07	5.49	5.48	5.43	5.44	5.40	5.41	5.36
100	5.63	5.56	5.59	5.59	5.67	5.67	5.70	5.68	5.71	5.76	5.82	5.81	6.32	6.31	6.25	6.24	6.15	6.19	6.10
105	6.65	6.44	6.47	6.44	6.60	6.56	6.58	6.53	6.57	6.67	6.87	6.90	7.47	7.44	7.38	7.32	7.25	7.28	7.18
110	7.54	7.33	7.37	7.31	7.48	7.48	7.49	7.46	7.52	7.58	7.83	7.87	8.46	8.44	8.36	8.28	8.26	8.26	8.17
115	8.45	8.32	8.33	8.24	8.37	8.40	8.43	8.43	8.56	8.54	8.76	8.82	9.43	9.42	9.31	9.18	9.10	9.11	9.05
120	9.56	9.42	9.43	9.30	9.37	9.40	9.49	9.53	9.63	9.66	9.83	9.91	10.5	10.5	10.4	10.2	10.0	10.0	10.0
125	10.8	10.6	10.6	10.5	10.5	10.5	10.7	10.8	10.8	10.9	11.1	11.2	11.8	11.7	11.6	11.3	11.1	11.1	11.2
130	12.2	12.0	12.1	11.9	11.9	11.9	12.0	12.2	12.3	12.4	12.6	12.6	13.1	13.0	12.9	12.6	12.4	12.3	12.4
135	13.8	13.6	13.6	13.4	13.4	13.4	13.5	13.7	13.7	14.0	14.1	14.1	14.5	14.4	14.1	13.8	13.6	13.6	13.7
140	15.3	15.2	15.1	14.9	15.0	15.0	15.1	15.2	15.4	15.7	15.8	15.7	15.9	15.7	15.4	15.1	14.9	14.9	15.0
145	16.9	16.9	16.7	16.5	16.7	16.7	16.8	16.7	17.1	17.3	17.4	17.2	17.2	16.9	16.6	16.3	16.2	16.2	16.2
150	18.3	18.4	18.4	18.1	18.2	18.3	18.4	18.5	18.8	18.8	18.8	18.6	18.3	18.0	17.6	17.4	17.2	17.3	17.3
155	19.2	19.5	19.6	19.3	19.3	19.5	19.7	19.9	20.0	19.9	19.7	19.5	19.2	18.9	18.6	18.2	18.1	18.1	18.1
160	20.1	20.4	20.5	20.5	20.7	20.9	21.0	21.1	21.2	21.0	20.8	20.5	20.1	19.9	19.6	19.3	19.1	19.1	19.1
165	21.0	21.5	21.6	21.7	22.1	22.3	22.3	22.5	22.5	22.4	22.0	21.7	21.4	21.3	21.0	20.7	20.4	20.4	20.3
170	22.0	22.3	22.6	23.0	23.4	23.6	23.6	23.6	23.5	23.3	23.0	22.8	23.0	23.0	22.9	22.6	22.5	22.3	22.0
175	22.0	22.3	22.5	22.7	22.8	23.0	23.0	23.0	22.8	22.6	22.4	22.1	22.3	22.1	22.0	21.8	21.9	21.9	22.0
180	21.9	22.1	22.0	22.0	22.0	22.0	22.0	21.9	21.9	21.8	21.7	21.7	22.0	22.0	22.1	22.0	22.0	22.0	22.0

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:QiuMing
Test Date:2015-10-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:5.920m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:

Table--2

UNIT: cd

C(DEG) γ (DEG)	285	300	315	330	345														
0	2434	2434	2434	2434	2434														
5	2353	2360	2355	2358	2352														
10	2140	2150	2142	2151	2141														
15	1843	1858	1846	1862	1848														
20	1530	1548	1537	1555	1551														
25	1425	1437	1454	1458	1461														
30	1599	1608	1584	1587	1548														
35	984	986	982	979	959														
40	811	814	812	806	802														
45	571	593	580	583	555														
50	61.8	64.1	64.1	64.7	65.2														
55	43.6	46.3	46.1	46.0	44.5														
60	27.4	28.7	28.5	28.6	27.7														
65	17.1	17.6	17.6	17.6	17.0														
70	8.86	9.05	8.91	8.93	8.61														
75	5.72	5.70	5.71	5.71	5.73														
80	5.72	5.69	5.70	5.69	5.71														
85	5.83	5.79	5.80	5.78	5.81														
90	5.56	5.79	5.50	5.70	5.18														
95	5.37	5.34	5.38	5.36	5.39														
100	6.15	6.11	6.19	6.15	6.17														
105	7.24	7.25	7.40	7.34	7.33														
110	8.22	8.24	8.38	8.34	8.32														
115	9.16	9.26	9.29	9.24	9.21														
120	10.2	10.3	10.3	10.3	10.2														
125	11.4	11.4	11.5	11.4	11.5														
130	12.7	12.7	12.8	12.8	12.8														
135	13.9	14.0	14.2	14.1	14.2														
140	15.2	15.4	15.5	15.5	15.7														
145	16.4	16.6	16.8	16.9	17.1														
150	17.4	17.6	17.8	18.0	18.3														
155	18.3	18.5	18.7	18.9	19.1														
160	19.3	19.4	19.6	19.8	20.1														
165	20.4	20.5	20.7	20.8	21.0														
170	22.0	22.1	22.2	22.2	22.3														
175	22.1	22.2	22.2	22.2	22.3														
180	21.9	21.9	21.8	21.7	21.7														

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:QiuMing
Test Date:2015-10-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:5.920m [K=1.0000]
Remarks: